

DATA SHEET

F34

F34 SQUARE TRUSS

TECHNICAL DATA

Chord diameter: 50mmØ
 Wall thickness: 2mm
 4 x Conical Spigots included.

LINEAR

CODE	LENGTH	WEIGHT
GT F34L025	0.25m	2.9kg
GT F34L029	0.29m	3.0kg
GT F34L040	0.4m	4.7kg
GT F34L050	0.5m	4.9kg
GT F34L075	0.75m	7.0kg
GT F34L100	1.0m	7.5kg
GT F34L125	1.25m	8.6kg
GT F34L150	1.5m	9.7kg
GT F34L200	2.0m	12.0kg
GT F34L250	2.5m	14.0kg
GT F34L300	3.0m	16.0kg
GT F34L350	3.5m	19.0kg
GT F34L400	4.0m	21.0kg
GT F34L450	4.5m	23.6kg
GT F34L500	5.0m	25.9kg

Custom lengths and radials can be manufactured to order.




Contact us for more info.

Sydney (02) 9649 2266
Melbourne (03) 9645 2266
Brisbane 0419 777 877
Perth 0419 898 999
Email info@dq.com.au

Check out our website

dq.com.au

INCLUSIVE



LOAD TABLE

Span m	Uniform distribution load kg / m	Centre point load kg	point load in third-point kg	point load in quarter-point kg	point load in fifth-point kg
4.0	510	940	639	506	401
5.0	350	778	538	419	330
6.0	245	661	464	353	279
7.0	180	573	406	303	241
8.0	137	503	360	265	212
9.0	108	448	322	234	188
10.0	86	402	290	209	169
11.0	70	364	263	188	153
12.0	59	330	240	171	138
13.0	48	301	220	156	127
14.0	41	276	203	142	116
15.0	35	253	186	130	107
16.0	30	233	172	120	98
17.0	26	215	160	111	90
18.0	23	198	148	102	83

The weight of the truss is considered in the load table.

Technical changes and errors are reserved



FOLLOW US:



DESIGN QUINTESSENCE
 excellence in staging products and design

